



## Features

The Silverglow range is constructed in 316 stainless steel with high Impact acrylic UV stabilised diffuser. These materials withstand most industrial agents and are able to be used in the dairy, meat, and other food production areas.

2hr Emergency Maintained and UPS supplied Emergency options available to order.

A retro fit LED gear tray available for older T8 Fluorescent installations. Only for use with drop lens diffuser.

Ceiling Surface Mount, Wall Mount, Suspended, Ceiling Corner Mount

Flat or Peaked Top

## Benefits:

- Can withstand most industrial cleaning agents
- A retro fit LED gear tray available for older T8 Fluorescent installations
- 4ft and 5ft Options
- LED
- Energy saving
- Long life

## Applications

Suitable for Hygiene areas such as freezing works, bakeries and general food handling or refrigerated storage areas.

## Lifetime

L70 50000hrs B10

5 yr warranty

230 V  
50 Hz

LED




For technical details, see page 2

## RX Silverglow Product Range

|   |  |
|---|--|
| <b>WATTS</b>                                    | 40W for 4ft, 80W for 5ft   |
| <b>LUMEN OUTPUT</b>                             | N/A  |
| <b>EFFICACY</b>                                 | N/A  |
| <b>CCT &amp; RX</b>                             | 4000k  |
| <b>CRI</b>                                      | >80  |
| <b>BEAM ANGLE</b>                               | N/A  |
| <b>IP RATING</b>                                | 54   |
| <b>IK RATING</b>                                | N/A  |
| <b>IC RATING</b>                                | N/A  |
| <b>IES FILES AVAILABLE?</b>                     | Yes  |
| <b>UGR</b>                                      |  |
| <b>DIMMING / CONTROLS / DRIVER</b>              | Non Dimmable   |
| <b>LIFETIME</b>                                 | L70 50000hrs B10   |
| <b>WARRANTY</b>                                 | 5 years  |
| <b>DIMENSIONS L,W,H</b>                         | 1351mm x 145mm x 236mm   |
| <b>CUTOUT</b>                                   |  |
| <b>WEIGHT</b>                                   |  |
| <b>MATERIALS</b>                                | 316 Stainless Steel & Acrylic                                      |
| <b>BODY COLOUR</b>                              | Stainless Steel  |
| <b>MOUNTING OPTIONS</b>                         | Ceiling Surface Mount, Wall Mount, Suspended, Ceiling Corner Mount |
| <b>STANDARDS &amp; RATINGS EG CA</b>            |  |
| <b>CONNECTION EG FLEX &amp; PLUG / TERMINAL</b> |  |

| ORDER CODE     | DESCRIPTION   |
|----------------|---|
| REX651220LEDP  | RX SILVERGLOW LED 2X20W 4FT PEAK TOP DROP DIFFUSER              |
| REX651220LEDFS | RX SILVERGLOW 6512 LED 2X20W 4FT NOM FLAT SIDES & TOP FLAT DIFF |
| REX651220LEDWM | RX SILVERGLOW 6512 LED 2X20W 4FT WALL MOUNT FLAT DIFFUSER       |
| REX651240LEDFS | RX SILVERGLOW LED 2X40W 5FT NOM FLAT SIDES & TOP FLAT DIFF      |
| REX651240LEDP  | RX SILVERGLOW LED 2X40W 5FT NOM PEAK TOP FLAT DIFFUSER          |
| REX651240LEDWM | RX SILVERGLOW LED 2X40W 5FT NOM WALL MOUNT FLAT DIFFUSER        |


## Photometric diagrams



## Accessories




DIFFUSER CLIP 1 SET PER BODY  
REX65125CLIPKIT



4FT DIFFUSER DROP LENS  
REX6512D4



4FT DIFFUSER FLAT SHEET CLR 131  
REX6512D4CF



5FT DIFFUSER DROP LENS  
REX6512D5



5FT DIFFUSER FLAT SHEET CLR 161  
REX6512D5CF



GEAR TRAY 2X40W LED 5FT  
REXGT651240LED



GEAR TRAY 2X20W LED 4FT  
REXGT651220LED

## Dimensions

