NZ POISONS CENTRE 0800 764 766 | NZ EMERGENCY SERVICES: 111 - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

CRC(NZ) Marker Pens

INGREDIENTS		CAS NO	%	TWA	
xylene		1330-20-7	30-60	217 mg/m3	
GHS	DG	PROPERTIES			
<u>ی (ا</u>	UN No: 1263 Hazchem Code: •3Y DG Class: 3 Subsidiary Risk: Not		Liquid. Does not mix	with water.Flammable.	
\mathbf{v}	3 Applicable Packing Grou				
HEALTH HAZA					
\neg					
Determined by			Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.		
Chemwatch		Eye:	Wash with running water.		
using GHS/HSNO criteriaGazetted by EPA New	3.1C, 6.1D (dermal), 6.1D (oral), 6.3A, 6.4A, 6.8B, 6.9B, 9.1D,	9B, 9.1D, Skin:	Remove contaminated clothing. Wash with soap & water.		
	9.3C	Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.		
Zealand Signal word:	Warning	Advice To Doctor:	Evaluate for respiratory distress. NO adrenalin.	Consider lavage with cuffed tube	
Hazard statement(s):	H302 Harmful if swallowed.	Fire Fighting:			
	H312 Harmful in contact with skin.		Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.		
	H315 Causes skin irritation.				
	H319 Causes serious eye irritation.	Spills and			
	H361 Suspected of damaging fertility or the unborn	child. Disposal:			
	H371 May cause damage to organs.				
	H373 May cause damage to organs through prolong repeated exposure.		SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS		
	H401 Toxic to aquatic life.				
	H413 May cause long lasting harmful effects to aqua	itic life.			
	H433 Hazardous to terrestrial vertebrates.				
	H226 Flammable liquid and vapour.	x — Must not be s	+ X +	+ +	
PRECAUTIONS	S FOR USE	0 — May be stored	I together with specific prevention	IS	
M A		above may not be re dangerous goods an	other risk factors, compatibility as elevant to storage situations, partic e stored and handled. Reference	cularly where large volumes of should be made to the Safety Da	
Appropriate engineering	Local Exhaust Ventilation recommended.	Sheets for each sub	Sheets for each substance or article and risks assessed accordingly.		

Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.TEFLON
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point.
En disemment.	Llawsful to accustic experience

Environment: Harmful to aquatic organisms.

 Chemwatch:
 4758-26

 Print Date:
 12/10/2021

 Issue Date:
 01/11/2019