

Product data sheet

Characteristics

PDL56C320RCD30LERO

RCD Protected Socket, 20A, 240V, 3-Round Pin, 2-Gang, Resis Orange



Main

Range of product	56 Series™
Product or component type	Residual current device switch
Control type	Push-button




Complementary

Material	PBT (polybutylene terephthalate)
Colour tint	Orange
Surface finish	Gloss
Installation direction	Vertical
Width	95 mm
Height	191 mm
Rated current	20 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Network number of phases	1 phase
Number of gangs	2 gangs
Pin number	3
Device composition	Round pin
Mounting mode	Surface mounted
Fixing center	84 x 180 mm
IP degree of protection	IP67
Ambient air temperature for operation	-10...40 °C
Quantity per set	Set of 2
Type of packing	Carton

Packing Units

Package 1 Weight	585.000 g
------------------	-----------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation

 [China RoHS Declaration](#)

Environmental Disclosure

 [Product Environmental Profile](#)
