

Exit and Emergency Luminaires

EZYLEDLP/WP - All-in-One Weatherproof Exit

A Premium Lithium 4W LED ceiling mounted all-in-one exit comes complete with all variations of running man decals. The weatherproof casing is manufactured from high impact polycarbonate to withstand the harshest environmental and weather conditions.



Features and Benefits

- Weatherproof design with IP65 Classification
- In built Sentinel Automatic testing capability
- High output LEDs for bright consistent & efficient light distribution.
- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximize battery life.
- Complete with all variations of the "Running Man" decal pack with a 24m viewing distance.
- Over 2 hours runtime in emergency mode.
- For sub-zero applications a remote box version is available upon request.
- Designed and manufactured in accordance to AS/NZS 2293



EZYLEDLP/WP		
Input	Operating Voltage / Frequency	230V / 50Hz
Output	LED Array	12 x LED
	Light Source	LED
	Function	Maintained
	Power Consumption	4W
Battery	Type	LiFePO ₄
	Charger	Variable current CV
	Protection	Charger overcharge and low voltage disconnect
	Emergency Runtime	2 hours*
Physical	IP Classification	IP65
	Weight	2kg
	Dimensions (LxHxW)	430x300x160mm
	Construction	Exit: Glass-filled ABS. Weatherproof case: Polycarbonate
Installation	Mounting	Ceiling
Environment	Temperature	0°C - 40°C
	Relative Humidity	0 - 95%
Conformance	C0	D3.2
	C90	E2.5
	Standards	AS/NZS 2293, AS/NZS 60598, AS/NZS CISPR15
Warranty	Duration	Fitting: 5 Years / Battery: 3 Years
Intelligence	Sentinel	In-built
	WiNetRF	Compatible

*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORY	DESCRIPTION
31511A	Replacement battery for EZYLEDLP

SPACING TABLE	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0
C0 - D3.2 (m)	6.5	6.6	6.6	6.5
C90 - E2.5 (m)	5.6	5.8	5.8	6.0

*Refer to AS/NZ 2293 for complete spacing table.