

PRODUCT DATASHEET

DULUX S 9 W/4000K G23

OSRAM DULUX S | Short CFLni, with 2-pin base for CCG operation



AREAS OF APPLICATION

- Ideal for cost-effective creative illumination and decoration
- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

PRODUCT BENEFITS

- Extremely economical
- Good quality of light
- Extremely low profile
- Long service life
- Improved maintenance

PRODUCT FEATURES

- Color rendering index $R_a \geq 80$
- Short and compact pin-base lamps with single-turn tubes
- Single-ended two-pin plug-in G23 base



TECHNICAL DATA


Electrical data

Rated wattage	9.00 W
Nominal wattage	9.00 W

Photometrical data

Luminous flux at 25 °C	570 lm
Light color (designation)	LUMILUX Cool White
Color temperature	4000 K
Color rendering index Ra	80

Dimensions & weight



Diameter	12.0 mm
Overall length	167.0 mm
Length	167.0 mm
Outer bulb	T12X3

Lifespan

Nominal lamp life time	8000 h
Rated lamp life time	8000 h

Additional product data

Base (standard designation)	G23
Mercury content	1.3 mg

Capabilities

Dimmable	No
-----------------	----

EQUIPMENT / ACCESSORIES

- Suitable for operation on conventional control gear

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321664310	Folding carton box 1	36 mm x 23 mm x 171 mm	44.00 g	0.14 dm ³
4008321664327	Shipping carton box 10	190 mm x 53 mm x 184 mm	492.00 g	1.85 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.