

Cable tie UNITY UV RESISTANT black 433 x 4.8 mm (x 100)



Characteristics

Length : **430**
 Width : **4.8**
 Thickness : **1.3**
 Maximum clamping Ø : **110**
 Traction strength : **222**
 Quantity per bag : **100**

Norms

> EN 62275

Benefits

- These cable ties last 3-4 times longer than standard cable ties exposed to UV light.

Compliance marks



GENERAL INFORMATION

Technical details

Polyamide 6.6 with additive guaranteeing resistance to UV rays.
 Operating temperature (°C): -40 to +85.
 Installation temperature (°C): > = 0.
 Raw material flammability: UL94 V-2.

Colour: black.

Application(s)

For attaching outdoor cables exposed to UV light.

LOGISTIC INFORMATION

Packaging



Polybag with colored label

Height (cm) : 5
 Length (cm) : 54
 Depth (cm) : 13
 Net weight (kg) : 0.30
 Gross weight (kg) : 0.32



Outer package 1



Carton box

Height (cm) : 20
 Length (cm) : 57
 Depth (cm) : 38
 Net weight (kg) : 12.12
 Gross weight (kg) : 14.05



Outer package 2



Pallet

Height (cm) : 95
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 224.79
 Gross weight (kg) : 240.79

