

ARDRICH A260

HIGH EFFICIENCY - ANTIMICROBIAL

A260M (WHITE/SS) HD15300

A260SP (STAINLESS STEEL) HD15304

- **FAST DRY TIME**
- **1.2 MM 304 STAINLESS STEEL**
- **ANTIMICROBIAL INFUSED PLASTICS**
- **FULLY AUTOMATIC INFRA-RED OPERATION**
- **ENERGY EFFICIENT - VERY LOW OPERATING COST**
- **SLIM UNOBTRUSIVE PROFILE**
- **LONG LIFE MOTOR AND CARBON BRUSHES**

SAFE SURFACES. Our revolutionary antimicrobial infused components inhibit the growth of microbes including Staphylococcus and E.coli. Components are manufactured from special resins using EPA approved silver ion technology that infuses plastic parts and coatings with antimicrobial properties.

SPECIFICATIONS

Construction: Enclosure - 1.2 mm 304 Stainless Steel, Base - ABS FR, Fan Housings - FR, Outlet - Nylon FR.
All plastics are flame retardant to UL94 VO, Class I double insulated, enclosure splash/drip proof to IPX3, non-corrosive.
Gross weight 3.33 kgs. Shipping weight 3.61 kgs.
Electrical rating 220-240 V~ 50-60Hz, 2.19 kW, 9.5AMP
Noise level 69 dB. Air volume 5.4 M3/min. Air velocity 175 km/hr.

PLANNING

Generally, one hand dryer is recommended for every two hand basins. For heavy use in large washrooms, use two hand dryers for every three basins.

ELECTRICAL SAFETY APPROVALS

AS3304, AS3300, NZ6362, NZ6300, IEC335-2-23:1996, IEC 335-1:1991 incl Amend 1, EN55014, EN50082-1, EN60555-2/3, International CB Text Certificate No. AU0182, Certificate of suitability No. Q070141

ELECTRICAL CONNECTION & ADDITIONAL NOTES

This dryer is a Class I product and is required to be earthed/grounded. Dryers are provided with a supply cord and plug. Dryer(s) may be fixed wired. Wiring should emerge from the wall at the position marked - Fixed wiring entry.

TOTAL SATISFACTION WARRANTY

Electronic Control Only Warranty – 5 year
All other components - 5 years

DISABLED PERSON COMPLIANT 

EMC COMPLIANT  Z184

TECHNICAL



A260SP

Polished 304 Stainless Steel



A260M

Gloss White Powder Coat over 304 Stainless Steel

ARDRICH HAND DRYERS



ARDRICH A260

HIGH EFFICIENCY - ANTIMICROBIAL

A260M (WHITE) HD15300

A260SP (STAINLESS STEEL) HD15304



A260M



A260SP

RECOMMENDED MOUNTING HEIGHTS

From the floor to the bottom of the dryer:

Men's washrooms -	1200mm
Women's washrooms -	1150mm
Children's washrooms - ages up to 10	860mm
Children's washrooms - ages up to 16	1120mm
Disabled person's washrooms -	1015mm

DRYER DIMENSIONS

Height -	273 mm
Width -	256 mm
Depth -	173 mm

