

## Product data sheet

### Characteristics

# PDL56CV432LECG

## 56 Series Combination - 4 Pin - 32A - 500V- Less Enclosure



### Main

Product or component type	Switch and socket-outlet
Device short name	PDL56CV432LECG
Plug, socket category	Low voltage
Poles description	3P + E
Control type	Rotary knob
Rotary handle padlocking	2 padlocks 8 mm
Network type	AC
Outlet standard	Australian/New Zealand

### Complementary

Mounting mode	Surface mounted
[In] rated current	32 A
Pin number	4 pins
Shape of pin	Tubular
[Ue] rated operational voltage	500 V
Network frequency	50 Hz
Protection type	Without protection
Material	Polycarbonate
Contacts material	Pins: brass
Connections - terminals	Screw terminals
Cable cross section	1...16 mm <sup>2</sup>
Net weight	0.551 kg
Height	190.0 mm
Width	95.0 mm
Depth	60.0 mm
Colour	Body: grey (RAL 7035) Rotary handle: dark grey




### Environment

Standards	AS/NZS 3133 AS/NZS 3123
Ambient air temperature for operation	-25...75 °C
Ambient air temperature for storage	-25...75 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.551 kg
Package 1 Height	75 mm
Package 1 width	95 mm
Package 1 Length	190 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>