

Product data sheet Characteristics

PDL56PA416K

Plug - Angled, 16A, 250V, 4-Round Pin, Keyway, Clear/Orange





Main

| Range | 56 Series |
|---------------------------|-----------|
| Product or component type | Plug |

Complementary

| Rated current | 16 A |
|---------------------------------------|----------|
| [Ue] rated operational voltage | 500 V |
| Material | Plastic |
| Colour tint | Orange |
| Surface finish | Gloss |
| Network frequency | 50 Hz |
| Network number of phases | 3 phases |
| Pin number | 4 |
| Ambient air temperature for operation | -4055 °C |
| Cable cross section | 716 mm² |
| Quantity per set | Set of 4 |
| Type of packing | Carton |

Environment

| IP degree of protection | IP66 |
|-------------------------|------|
| | |

Packing Units

| Package 1 Weight | 0.332 kg |
|------------------|----------|
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|--------------------------------|--|
| REACh Regulation | ☑ REACh Declaration | |
| EU RoHS Directive | Compliant EEU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | ₫Yes | |
| China RoHS Regulation | China RoHS Declaration | |
| Environmental Disclosure | Product Environmental Profile | |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.