OUTDOOR



CHASE 20W LED Double Spot Wall Light, Standard and PIR sensor, CCT selectable 3000K, 4000K, 6000K, IP 54 White and Black Housing

These great looking outdoor LED spot lights provide both energy efficiency and security, available in both Black & White. Quicker & Easier fit off with separate deeper base with a push in connection style. Available in Standard or with built in PIR which has adjustable sensitivity, hold time & lux settings for different environmental conditions.



Product Code:	STANDARD	PIR
White Black	RCH20CCT3-01 RCH20CCT3-04	RCH20CCT3P-01 RCH20CCT3P-04
Total Power (W):	19.4/18.7/19.3	19.4/18.7/19.3
Total Light Output (lm):	1,790/2,110/1,960	1,790/2,110/1,960
Efficacy (lm / cctW):	93/113/102	93/113/102
Illuminance at 1m (lux):	780/870/770	780/870/770
Beam Angle (deg):	100	100
CCT (K):	3,000/4,000/6,000	3,000/4,000/6,000
CRI (Ra):	80	80
Rated Life (hrs):	30,000	30,000
Warranty (yrs):	3	3
Ingress Protection (IP):	54	54
Operating Temperature (°C):	-20 ≤ Ta ≤ +40	-20 ≤ Ta ≤ +40
Operating Voltage (Vac):	220-240	220-240
Height (mm):	148	208
Length (mm):	182	183
Width (mm):	201	201
Weight (kg):	0.59	0.64

Cone Illuminance Diagram:




Diagram for RCH20CCT3-01 in 4,000K. Other diagrams available on request

Features:

- CCT3 3000k, 4000k & 6,000k
- Quick Connecting base / fitting
- IP54 Fitting & PIR Sensor
- Manual Override (PIR Sensor)

Applications:


- Garages & Workshops
- Patio & Deck areas
- Garden & driveway paths
- Sign Illumination

Construction:


- Polycarbonate housing & trim
- Polycarbonate lens covers


PIR Settings:

Time Duration
Lux Adjustment range
Mounting Height range
Detection Angle
Sensor Detection range
10s to 10min
0 - 2000 Lux
1.5m to 3m
150 degrees
12m



Sensor Detection Range:





Standards & Approvals:

Complies with: SAA & RCM