

# TPS Three Core +E (Blue)

CU TPS 3X 2.5+E BU 5HM

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

**Nexans Ref.:** ENZP07A5003BFRJ

**Country Ref.:** 4169.5

Stranded plain annealed copper, 450/750 V PVC insulated, PVC Flat Sheathed to AS/NZS 5000.2

## DESCRIPTION

TPS Blue is a durable and robust cable specifically designed for air conditioning. What's new? This product is an extension of our current TPS cable, with the added benefit of a blue coloured sheath for easy identification during installation.



## STANDARDS

**National AS/NZS 5000.2**



Conductor flexibility  
Class 2



Rated Voltage Uo/U (Um)  
450 / 750 V



Max. conductor temp. in service  
90 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 27/01/22 www.nexans.co.nz Page 1 / 2

# TPS Three Core +E (Blue)

CU TPS 3X 2.5+E BU 5HM

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

## CHARACTERISTICS

### Construction characteristics

With Green/Yellow core	Yes
Sheath colour	Blue
Conductor flexibility	Class 2
Conductor material	Copper
Conductor shape	Circular
Core identification	Red, White, Blue, Green/Yellow
Insulation	V-90
Outer sheath	PVC
Type of conductor	Class 2

### Dimensional characteristics

Number of cores	3
Conductor cross-section	2.5 mm <sup>2</sup>
Earth conductor cross section	2.5 mm <sup>2</sup>
Nominal overall diameter	5.25 x 15.1
Approximate weight	0.18 kg/m
Cable length	500 m
Nominal insulation thickness	0.7 mm
Nominal outer sheath thickness	1.0 mm

### Electrical characteristics

Rated Voltage U <sub>o</sub> /U (Um)	450 / 750 V
Conductor AC resistance at 50 Hz	- Ohm/km
Inductive reactance at 50Hz	- Ohm/km
Max. DC resistance of the conductor at 20°C	7.41 Ohm/km

### Usage characteristics

Max. conductor temperature in service	90 °C
---------------------------------------	-------