

Industrial Suspended/Surface Mount  
**LEDE Select 223W High Output High Bay**

P701



**SPECIFICATIONS**

<b>DIMENSIONS</b>	D380 x H110mm
<b>COLOUR TEMP</b>	4000K Natural White
<b>LUMENS</b>	120W / 22,000lm 150W / 26,500lm 170W / 30,000lm 200W / 34,000lm <b>223W / 38,000lm (default factory setting)</b>
<b>CRI</b>	80
<b>LIFESPAN</b>	57,000 hours (L80 B10)
<b>BEAM ANGLE</b>	90°
<b>MATERIAL</b>	Aluminium / PC
<b>IP RATING</b>	IP65
<b>IK RATING</b>	IK08
<b>DRIVER</b>	Incorporated, modular quick release plug and play driver pre-wired with 1500mm lead and three pin plug.
<b>TLAs</b>	"Flicker-free", Pst≤1.0; SVM ≤4 at Full Load to avoid stroboscopic effect in rotating machinery
<b>DIMMING</b>	Individually Dimmable to 10% (in 5% intervals) via remote control when installed with plug and play sensor accessory
<b>SENSOR</b>	Motion and Daylight sensor accessory available. Remote adjustable power output, detection area, hold time, daylight threshold, stand-by period and stand-by dimming level. <b>Default sensor factory settings:</b> Detection area: 100%, Hold time: 3min, Daylight threshold: 200 lux, Stand-by period: 10s, Stand-by dimming level: 50%.
<b>APPLICATION</b>	Industrial High bay
<b>POWER FACTOR</b>	0.95
<b>AMBIENT TEMP</b>	-30°C to +50°C
<b>WEIGHT</b>	3200g
<b>WARRANTY</b>	5 Year Warranty

<b>&lt;38,000 LUMENS</b>	<b>&lt;223 WATTS</b>	<b>AC 240V</b>
--------------------------	----------------------	----------------

**AVAILABLE IN**

DESCRIPTION	CODE
4000K, Selectable Output Driver	P701 4KA

**ACCESSORIES**

DESCRIPTION	CODE
Sensor	P700 S1
Remote Control for Sensor, Digital Display	P700 R1
Surface Mount Bracket	P700 SMB
250mm Chain with Snap Links	P700-CH250
500mm Chain with Snap Links	P700-CH500
1000mm Chain with Snap Links	P700-CH1000
Casambi control module	P700 CAS1

**P701 INRUSH CURRENT 60A SURGE TIME 300µs**

MCB Type	B10	B13	B16	B20
Max. connected lights	3	3	4	6
	C10	C13	C16	C20
	6	8	10	12