

# ROBUS®

HILUME LED FLOOD LIGHT, IP65, BLACK, 4000K,  
C/W 1M FLEX

RHL1040-04 RHL2040-04 RHL10040-04  
RHL3040-04 RHL5040-04

PLEASE READ INSTRUCTION BEFORE COMMENCING INSTALLATION AND RETAIN FOR FUTURE REFERENCES.

! Electrical products can cause death or injury, or damage to property. If in any doubt about the installation or use of this product, consult a competent electrician

**Note:**

Product technical information and specification may change over time without prior notification. For the latest technical information please visit our web site [www.robust.com.au](http://www.robust.com.au)

-20°C < Ta < +40°C, 220-240V ~ 50/60Hz, Class I, IP65  
Luminaire is non-dimmable

## Installation

1. Ensure mains supply is switched off before commencing work.
  2. Select suitable location for luminaire.
  3. Mark wall with appropriate fixing positions. Before drilling, ensure that the hole does not impinge on pipe work, cables or other building services.
  4. Attach luminaire and fix bracket by tighten screws, then adjust to desired angle. Ensure that it is secure.
  5. The luminaire is supplied with 1m of rubber cable. Using suitable IP rated enclosure terminate Brown (Live), Blue (Neutral) and Green/Yellow (Earth) to switch supply.
  6. This product has no user serviceable parts. If any part is damaged, disconnect from mains and discontinue use.
- Note: No "fixings screws provided", please use appropriate fixing screws.

The Installation must be carried out by a qualified electrician

LED Group Australasia  
9/210 Queensport Road North  
Murarrie  
QLD 4172  
Australia

Tel: 07 3890 5444  
Fax: 07 3890 4777  
Email: [purchases@robust.com](mailto:purchases@robust.com)  
Website: [www.robust.com.au](http://www.robust.com.au)

LED Group  
Crowe Hogwarth  
72 Trafalgar Square  
NELSON 7010  
New Zealand

Tel: +64 0508 533 335  
Email: [nz\\_purchases@robust.com](mailto:nz_purchases@robust.com)  
Website: [www.robustled.co.nz](http://www.robustled.co.nz)



Issue 1 071119

