


Product data sheet Characteristics

LVS08006

Wall mounted enclosure, PrismaSeT G Pack 160, W 555mm, H 1080mm (6R), IP30, with front plates, for modular devices





Main Range PrismaSeT Range of product PrismaSeT G Product name PrismaSeT Pack 160 Product or component Enclosure type Device application Low voltage electrical distribution Enclosure type Modular enclosure pre-mounted Metal enclosure Indoor enclosure Enclosure/cubicle Wall-mounted enclosure - width 555 mm description Provided equipment 1 x enclosure 1 x earthing kit 6 x front plate 6 x modular rail Additional information Can be combined side by side and one on top of Type of front plate Modular Number of vertical 18 modules [50 mm] Number of horizontal 6 rows Number of 18 mm 24 modules per row Standards IEC 61439-1 IEC 61439-2 IEC 62208

ASTA EAC

Complementary

| Complementary | |
|--|--|
| [Ui] rated insulation voltage | 750 V on main rear busbars conforming to IEC 61439-2 |
| Network frequency | 50/60 Hz |
| [In] rated current | 160 A at 40 °C conforming to IEC 61439-2 |
| [lcw] rated short-time withstand current | 25 kA 1 s conforming to IEC 61439-1 |
| [lpk] rated peak withstand current | 53 kA conforming to IEC 61439-1 |
| Electrical insulation class | Class I |
| Material | Treated sheet steel |
| Protective treatment | Electrophoresis treatment and hot-polymerised polyester epoxy powder |
| Surface finish | Textured Matt |
| Colour | White (RAL 9003) |
| Width | 555 mm |
| Height | 1080 mm |
| Depth | 157 mm |
| Net weight | 16.06 kg |
| Quantity per set | Set of 1 |
| | |

Product certifications

Environment

| IP degree of protection | IP30 with front plate | |
|-------------------------|--|--|
| | IP40 with door | |
| | IP41 with door and canopy | |
| | IP43 with door, canopy and IP43 gasket | |
| IK degree of protection | IK07 with front plate | |
| | IK08 with transparent door | |
| | IK10 with plain door | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|---------|
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 17.3 kg |
| Package 1 Height | 17.5 cm |
| Package 1 width | 56.5 cm |
| Package 1 Length | 111 cm |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 5 |
| Package 2 Weight | 98.5 kg |
| Package 2 Height | 99.5 cm |
| Package 2 width | 80 cm |
| Package 2 Length | 120 cm |
| | |

Offer Sustainability

| Office Gustamushity | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | €Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |
| | |