

# Connexion SQUALE 25 kit for sealed connection up to 4 conductors of wire section 6 mm<sup>2</sup>

*Quick, waterproof, efficient*

## Aucun visuel

### Characteristics

Référence Nouvelle-Zélande : **BIZ710299**  
 Capacity 1 conductor (mm<sup>2</sup>) : **120-240**  
 Capacity 2 conductors (mm<sup>2</sup>) : **6-50**  
 Capacity 3 conductors (mm<sup>2</sup>) : **6-35**  
 Capacity 4 conductors (mm<sup>2</sup>) : **4-35**  
 Dimensions (mm) : **210 x 65**

### Norms

> IP X8

### Benefits

- IPX8 for immersed installations.
- Full range dedicated to residential and tertiary.
- Non toxic.

## GENERAL INFORMATION

### Technical details

Voltage: 0.6 to 1 kV.

### Application(s)

For connecting, insulating, sealing and protecting copper electrical cables.

Supplied with cable centring device and cable ties for holding conduits.

### Instructions

1. Strip and connect the cables.
2. Insert the separator and centre the cables in the enclosure.
3. Close the enclosure and lock in the conduits.

## TECHNICAL DOCUMENT(S)

### Technical documentation available on our website :

 SDS

## LOGISTIC INFORMATION

### Packaging



#### Carton box

Height (cm) : 10  
 Length (cm) : 23  
 Depth (cm) : 11  
 Net weight (kg) : 0.491  
 Gross weight (kg) : 0.491



### Outer package 1



#### Carton box

Height (cm) : 44  
 Length (cm) : 50  
 Depth (cm) : 38  
 Net weight (kg) : 11.784  
 Gross weight (kg) : 12.41



x 24

### Outer package 2



#### Pallet

Height (cm) : 105  
 Length (cm) : 80  
 Depth (cm) : 120  
 Net weight (kg) : 99.28  
 Gross weight (kg) : 130



x 192