

Product data sheet

Characteristics

PDLS120EM

1-Way Enclosed Main Switch; 20A, 240VAC, 50 Hz, 1P, White



Main

Range of product	S Series
Product or component type	Switch
Material	PC (polycarbonate)
Colour tint	White
Surface finish	Gloss

Complementary

Installation direction	Vertical
Width	82 mm
Height	165 mm
Depth	81 mm
Rated current	20 A
[Ue] rated operational voltage	240 V
Network frequency	50 Hz
Motor M-rating AS3133	M125
Number of poles	1
Mounting mode	Surface mounted
IP degree of protection	IP66
Cable cross section	16 mm ²
Quantity per set	Set of 1
Type of packing	Carton

Packing Units

Package 1 Weight	0.387 kg
Package 1 Height	80.000 mm
Package 1 width	85.000 mm
Package 1 Length	170.000 mm

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.