



## Red Indicator light 230VAC

SVN122M

### Main electrical features

Rated operational voltage Ue	230 V
Frequency	50/60 Hz

### Voltage

Rated insulation voltage	250 V
Rated impulse withstand voltage	4000 V

### Frequency

Frequency	50 to 60 Hz
-----------	-------------

### Power

Total power loss under IN	0,8 W
---------------------------	-------

### Materials

Colour	red
--------	-----

### Dimensions

Depth of installed product	62 mm
Height of installed product	83 mm
Width of installed product	17,5 mm

### Lighting control

Type of lamp	LED
--------------	-----

### Installation, mounting

Tightening torque	1,7Nm
-------------------	-------

### Connection

Connection cross-sect. flexible conductor	0,75 / 6mm <sup>2</sup>
Connection cross-sect. rigid cable	0,75 / 10mm <sup>2</sup>
Lamp socket type	Fix
Type of connection	with screw

**Standards**

---

European directive WEEE	not concerned
-------------------------	---------------

---

**Safety**

---

Protection index IP	IP20
---------------------	------

---

**Use conditions**

---

Operating temperature	-20 50 °C
-----------------------	-----------

---

Degree of pollution according to IEC 60664 / IEC 60947-2	3
--	---

---

Altitude	2000 m
----------	--------

---

Storage/transport temperature	-40 80 °C
-------------------------------	-----------

---