

# Recessed Fixed Downlight Kit Cevon Dark Art Round



R536



## SPECIFICATIONS

<b>DIMENSIONS</b>	D83 x H92mm
<b>CUT OUT</b>	Ø 76mm
<b>COLOUR TEMP</b>	3000K Warm White
<b>LUMENS</b>	White reflector 1090lm, Silver reflector 1000lm High Gloss Black 890lm, Gold 810lm, Matte Black reflector 865lm
<b>CRI</b>	97.8
<b>LIFESPAN</b>	>55,000 hours (L90 B20)
<b>BEAM ANGLE</b>	45°
<b>INTENSITY AT 2M</b>	460 lux / 1.6m beam width (3000K, White reflector)
<b>INTENSITY AT 3M</b>	205 lux / 2.5m beam width (3000K, White reflector)
<b>INTENSITY AT 4M</b>	115 lux / 3.3m beam width (3000K, White reflector)
<b>MATERIAL</b>	Aluminium, coated optic glass
<b>IP RATING</b>	IP44
<b>CLEARANCE</b>	25mm recommended for optimum lifespan. 0mm required. Rear of fitting may abut structural members and building elements.
<b>CLASSIFICATION</b>	IC Rated
<b>DRIVER</b>	DX Series Under Insulation Dimmable TRIAC Driver Included (pre-wired)
<b>INSTALLATION</b>	Cut holes with extra caution (5mm rim)
<b>APPLICATION</b>	Interior residential or commercial downlighting
<b>WARRANTY</b>	5 Year Warranty

**<1090**  
LUMENS

**14**  
WATTS

**AC**  
240V

UID™ Dimmable Under  
Insulation Driver Included

## COLOUR PARAMETERS

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg
3000K	97.8	98.3	94.8	102.2

## AVAILABLE IN

DESCRIPTION	CODE
White / White 3000K	R536 WW3K
White / High Gloss Black 3000K	R536 WB3K
White / Matte Black 3000K	R536 WMB3K
White / Gold 3000K	R536 WG3K
White / Silver 3000K	R536 WS3K
Black / High Gloss Black 3000K	R536 BB3K
Black / Matte Black 3000K	R536 BMB3K
Black / Gold 3000K	R536 BG3K
Black / Silver 3000K	R536 BS3K