

SPECIFICATIONS

DIMENSIONS	EV1200SD: L1200mm x W65mm x H86mm EV1500SD: L1500mm x W65mm x H86mm EV3000SD: L3000mm x W65mm x H86mm
COLOUR TEMP	3000K Warm White or 4000K Natural White
LUMENS	3000K Warm White: 1200mm/2800lm 1500mm/3500lm, 3000mm/7000lm 4000K Natural White: 1200mm/2900lm 1500mm/3625lm, 3000mm/7250lm
CRI	90+
LIFESPAN	60,000hr (L90)
UGR	Halcyon Everline Linear series are suitable for installations requiring UGR of less than 19.
BEAM ANGLE	80°
BINNING	3-step SDCM
FINISH	Black or White (Powder Coated)
MATERIAL	Aluminium, PMMA
IP RATING	IP20
IK RATING	IK02
APPLICATION	Residential/Commercial Interior
PRIMARY VOLTAGE	220-240V ~ 50/60Hz
DRIVER	Standard Non-dimmable driver incorporated, Dali available on indent
COMPLETE WITH	Pre-wired with 1700mm feed cable
WARRANTY	5 Year warranty

EV1200SD (Direct)


<2900 LUMENS **29 WATTS**

EV1500SD (Direct)


<3625 LUMENS **36 WATTS**

EV3000SD (Direct)

<7250 LUMENS **72 WATTS**



Direct



Everline Linear Individual Luminaires Direct (Down)

AVAILABLE IN

1200mm 29W, Individual Direct, Standard Driver

DESCRIPTION	CCT	COLOUR	CODE
1200mm Individual	4000K	White	EV1200SD W4K
	4000K	Black	EV1200SD B4K

1500mm 36W, Individual Direct, Standard Driver

DESCRIPTION	CCT	COLOUR	CODE
1500mm Individual	3000K	White	EV1500SD W3K
	3000K	Black	EV1500SD B3K
	4000K	White	EV1500SD W4K
	4000K	Black	EV1500SD B4K


3000mm 72W, Individual Direct, Standard Driver

DESCRIPTION	CCT	COLOUR	CODE
3000mm Individual	3000K	White	EV3000SD W3K
	3000K	Black	EV3000SD B3K
	4000K	White	EV3000SD W4K
	4000K	Black	EV3000SD B4K


Dali and 1-10V available on Indent order. MOQs apply.

INDIVIDUAL DIRECT OPTIONAL ACCESSORIES


DESCRIPTION	CODE
Ceiling Clip Surface Mount	EV CECL
Cable Suspension Kit 1500mm Direct only	EV CSUSD
Ceiling Rose Black	EV CRB
Ceiling Rose White	EV CRW



Ceiling Clip Surface Mount Direct Only



Ceiling Rose



Cable Suspension Kit 1500mm Direct Only