

Catalogue No: **2080-LCD**

M810 PLUG-IN LCD 1.5in DISPLAY KEYPAD

Automation Systems > Micro Programmable Controllers and Smart Relays > Smart Relays > Allen-Bradley® Micro810® Controllers > Micro 810® Accessories



1.5 Inch Plug-In LCD for Micro810 only, Display with Keypad, Smart Relay Configuration

- Flexible power supply options available (12V DC, 24V DC and 240V AC)
- 4A and 8A outputs eliminate the need for external relays
- Four inputs can be configured as 0-10V DC analogue inputs (DC Models only)
- Program download via USB programming port (2080-USB-ADAPTER required)
- Optional 1.5" local LCD for monitoring / modifying application data
- Optional LCD display also functions as a backup memory module
- Configure and run core smart relay function blocks without software (2080-LCD screen required)

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	Micro800 (Bul. 2080)
Component Type PLC & I/O	Accessory
Module Specific Functions	1.5" LCD Display and Keypad Module
Operating Temperature, Max	55 °C max
Operating Temperature, Min	-20 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
IP Rating	IP20

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-