



## Main

Device short name	MT100/160
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	ComPact NSX100 ComPact NSX160 Compact NSX100 DC Compact NSX160 DC PowerPact Multistandard EasyPact CVS100 EasyPact CVS160 PowerPact J PowerPact H
Control type	Standard
[Uc] control circuit voltage	110...130 V AC 50/60 Hz
Circuit breaker mounting mode	Fixed
Circuit breaker frame rated current	100 A 160 A

## Complementary

Control signal type	Maintained Impulse
Response time	< 700 ms (opening) < 80 ms (closing)
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Provided equipment	SDE adaptor
Locking options description	Padlocking in OFF position 1 to 3 padlocks Ø 5 to Ø 8

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.386 kg
Package 1 Height	10.5 cm
Package 1 width	12 cm
Package 1 Length	17.3 cm
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Weight	21.661 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------