

Thin wall 2/1 white heat-shrink tubing without adhesive 25/12.5 mm 4FT

Aucun visuel

Caracteristics

Référence Nouvelle-Zélande : **BIZ218067**

Color : **White**

Wall Ø before shrinking (mm) : **25**

Wall Ø after shrinking (mm) : **12.5**

GENERAL INFORMATION

Description

Thin wall 2/1 heat-shrink tubing without adhesive.

Technical details

Thin wall, 2/1 shrinkage in length 1.2 meter.

Heat-shrink tubing in flexible flame retardant polyolefin (except clear).

Working temperature: -45 °C to +125 °C (clear is -45 °C to +105 °C).

Shrink temperature: 120 °C (clear is 105 °C).

Dielectric strength (IEC 243): 15 kV/mm.

Tensile strength: 10.4 Mpa.

Rate voltage: 600 V.

Self-extinguishing in accordance with UL224 (except clear).

Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

ADDITIONAL INFORMATION

Color and diameter next pages.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 1.25

Length (cm) : 120

Depth (cm) : 3.8

Net weight (kg) : 0.065

Gross weight (kg) : 0.068



Outer package 1



x 10

Bag

Height (cm) : 16

Length (cm) : 120

Depth (cm) : 3.8

Net weight (kg) : 0.65

Gross weight (kg) : 0.68



Outer package 2



x 200

Carton box

Height (cm) : 16

Length (cm) : 130

Depth (cm) : 20

Net weight (kg) : 14.5

Gross weight (kg) : 15.1



Outer package 3



x 5600

Pallet

Height (cm) : 115

Length (cm) : 130

Depth (cm) : 80

Net weight (kg) : 406

Gross weight (kg) : 422.8

