

# PVC Neutral Screened Cables single core and two cores

CU NSCRN 2X 2.5 3.2 250M

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

**Nexans Ref.:** DAEP07PX302CXAB

**Country Ref.:** 5862.25

Cu conductors, PVC insulation, Cu wire neutral screen, Black PVC sheath. 0.6/1 kV. Made to AS/NZS 4961.

## DESCRIPTION

### Application

- Industrial, commercial and domestic applications
- For use in various situations to supply the main power from the point of supply to buildings, equipment, sheds, eg, switch board to main control cabinet, main between floors and buildings, cable cabinet to motor, etc.



## STANDARDS

**National AS/NZS 4961**



Conductor flexibility  
**Class 2**



Rated Voltage U<sub>0</sub>/U (Um)  
**0.6/1 (1.2) kV**



Cable flexibility  
**Rigid**



Max.conductor temp.in service  
**75 °C**

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 8/12/21 [www.nexans.co.nz](http://www.nexans.co.nz) Page 1 / 3

# PVC Neutral Screened Cables single core and two cores

CU NSCRN 2X 2.5 3.2 250M

## Contact

Sales and Customer Solutions  
sales.nz@nexans.com

## CHARACTERISTICS

### Construction characteristics

|                                |                    |
|--------------------------------|--------------------|
| Pilot wires                    | None               |
| Conductor material             | Copper             |
| Type of conductor              | Circular, stranded |
| Insulation                     | PVC                |
| Screen                         | Copper wire        |
| Outer sheath                   | PVC                |
| Colour                         | Black              |
| Conductor flexibility          | Class 2            |
| Conductor shape                | Circular           |
| Core identification            | White, Red         |
| With Green/Yellow core         | No                 |
| With smaller neutral conductor | No                 |

### Dimensional characteristics

|  |                     |
|--|---------------------|
| Number of cores                          | 2                   |
| Conductor cross-section                  | 2.5 mm <sup>2</sup> |
| Nominal overall diameter                 | - mm                |
| Nominal overall diameter                 | 11.5 x 15.3         |
| Gland Size (A2 or A2F)                   | 20                  |
| Gland Size (CX/Z)                        | 20                  |
| Nominal outer sheath thickness           | 3.2 mm              |
| Approximate weight                       | 0.28 kg/m           |
| Neutral conductor section (when smaller) | - mm <sup>2</sup>   |

### Electrical characteristics

|   |                 |
|---|-----------------|
| Max. DC resistance of the conductor at 20°C       | 7.41 Ohm/km     |
| Permissible short circuit current conductor 1s    | - kA            |
| Rated Voltage U <sub>o</sub> /U (U <sub>m</sub> ) | 0.6/ 1 (1.2) kV |

### Mechanical characteristics

|                   |       |
|-------------------|-------|
| Cable flexibility | Rigid |
|-------------------|-------|

### Usage characteristics

|                                       |       |
|---------------------------------------|-------|
| Max. conductor temperature in service | 75 °C |
|---------------------------------------|-------|













# PVC Neutral Screened Cables single core and two cores

CU NSCRN 2X 2.5 3.2 250M

Contact  
Sales and Customer Solutions  
sales.nz@nexans.com

## CURRENT CARRYING CAPACITIES SINGLE PHASE (IN AMPS) - TWO CORE PVC NEUTRAL

Copper conductor Circular stranded Insulation PVC Max. Conductor Temperature 75C

| Conductor cross-section<br>[mm <sup>2</sup> ]   |  Cu                        |  Cu            |  Cu  |  Cu |  Cu |  Cu |
|---|---|---|---|--|--|--|
| 2.5   | 26  | 25  | 23  | 28   | 28   | 13   |
|  Air Spaced from Surface, Unenclosed |  Air touching, unenclosed  |  Air enclosed |   |  |  |  |
|  Buried direct                       |  Buried in single-way duct |   |  Cable surrounded by thermal insulation, unenclosed |  |  |  |