ROBUS°

BARON 20W/40W LED BATTEN, IP20, CCT SELECTABLE 3000K, 4500K, 6500K

RBN2006CCT3N-01, RBN4012CCT3N-01

PLEASE READ INSTRUCTION BEFORE COMMENCING INSTALLATION AND RETAIN FOR FUTURE REFERENCE.

! Electrical products can cause death or injury, or damage to property. If in any doubt about the installation or use of this product, consult a competent electrician Note:

Product technical information and specification may change over time without prior notification. For the latest technical information please visit our web site www.robus.com.au

 -20° C < Ta < $+40^{\circ}$ C, 220-240V ~ 50/60Hz, Class I, IP20 Luminaire is non-dimmable.

Suitable for mounting on a normally flammable surface.

Installation

- 1. Ensure mains supply is switched off before commencing work.
- 2. Remove the cover at the CCT switch end by removing the screw.
- 3. Remove the diffuser.
- 4. Mark appropriate fixing points on wall or ceiling; check that fixings will not impinge on concealed cables or pipes before drilling holes.
- Connect supply cables to fitting terminal: Brown/Live to L, Neutral/Blue to N and Earth/Green Yellow to E.
- The default setting for the fitting is 3000K. Move switch to select 4500K or 6500K.
- WARNING: DO NOT CHANGE CCT WHEN THE FITTING IS ON!!
- 7. Refit the diffuser and the end cover. Ensure it is secure.

This product has no user serviceable parts. If any part is damaged, disconnect from mains and discontinue use

The Installation must be carried out by a qualified electrician

LED Group Australasia

9/210 Queensport Road North Tel: 07 3890 5444 Murarrie Fax: 07 3890 4777

QLD 4172 Email: purchases@robus.com Australia Website: www.robus.com.au

LED Group

Crowe Hogwarth Tel: +64 3668 5285

72 Trafalgar Square Email: nz_purchases@robus.com NELSON 7010 Website: www.robusled.co.nz New Zealand













