




## Inline Fans - Axial

The Hyper150 EC axial fan is the trusted leader in bathroom extraction. Now with an EC motor, other ongoing improvements and variable speed control with 10m control cable, Hyper150 continues to lead the field. 7 year warranty.


Ceiling mounted ID and ECO fans have a range of performance levels for short and efficient duct systems. 2 year warranty.

Classic HYPER150 EC	Duct (mm)	Fan Type	Max. Fan Watts (W)	Max. Fan Pressure (PA)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Sound dB(A)	Switching	Order Code
					(l/s)	(m <sup>3</sup> /hr)				
	150	EC Axial	18	91	105	380	0.17	38	Standard	FAN0085
	150	EC Axial	18	91	105	380	0.17	38	Variable Speed Controller**	FAN7000*

Classic	Duct (mm)	Fan Type	Max. Fan Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Sound dB(A)	Switching	Model	Order Code
					(l/s)	(m <sup>3</sup> /hr)					
	150	Axial	25	60	87	313	0.29	40	Standard	ID150S	FAN0090
									Timer	ID150T	FAN0091
	125	Axial	20	35	36	130	0.56	41	Standard	ID125S	FAN0060
									Timer	ID125T	FAN0061
100	Axial	20	25	23	85	0.87	41	Standard	ID100S	FAN0012	
								Timer	ID100T	FAN0013	

Classic ECONOMY	Duct (mm)	Fan Type	Max. Fan Watts (W)	Max. Fan Pressure (Pa)	Free Air Fan Performance		Specific Fan Power (W/l/s)	Sound dB(A)	Switching	Model	Order Code
					(l/s)	(m <sup>3</sup> /hr)					
	150	Axial	25	50	64	230	0.39	40	Standard	ECO150S	FAN2078

\*All data for FAN7000 at full speed

\*\*Euro flush-box for variable speed control switch – included

**Note:** Installed system performance is always influenced by duct length and layout

### Switching Options


**Standard** Remote switch (not supplied).

**Timer** Remote switch (not supplied). Fan continues operating for preset time after switching off.

## Inline Fans - Axial

### Dimensions (mm)

Model	A	B	C	D	E
<b>Hyper150 EC</b>	200	143	170	185	-
<b>ID150</b>	187	153	109	150	27
<b>ID125</b>	150	155	99	118	27
<b>ID100</b>	130	155	90	100	27
<b>ECO150</b>	187	153	109	150	27



Hyper150 EC Fans

ID & ECO Fans

### Technical

Model	Hyper150 EC	ID150	ID125	ID100	ECO150
<b>Supply</b>	220-240V AC, 50Hz				
<b>Sound Level</b>	38 dB(A)	40 dB(A)	41 dB(A)	41 dB(A)	40 dB(A)
<b>Max. Operating Temp</b>	45°C	40°C	40°C	40°C	50°C
<b>IP Rating</b>	IP44	IP44	IP44	IP44	IPX4