

PRODUCT SPECIFICATION

DESCRIPTION

The standard FibreFab W32 Lockable IP65 distribution box is supplied unloaded as standard and offers the ability to terminate 48 fibres housed in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable adaptor tray provides a neat and tidy solution for housing 48 SC simplex connections and splices. Integrated cable tie points are included to secure incoming cables. A locking feature for the door adds extra security when positioned in unsecure areas.



FEATURES

- IP 65 Rating for external use
- Lockable door for added security
- Integrated cable tie points for securing incoming cable
- Up to 48 splice & SC connection points
- Removable splice tray for easy installation
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Removable door for ease of installation
- Supplied with 48 heatshrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixings and tie wraps
- ROHS, REACH & SvHC compliant

SPECIFICATIONS

Height (mm)	420
Width (mm)	320
Depth (mm)	125
Net weight (kg)	1.8
Suitable for adaptor type	SC Simplex, LC Duplex
Number of Adaptor Positions	48
Splice Tray Type	48 Cores
Max. Splicing Capacity	96 Splices
Cable entry	2
Material	PC+ABS
Colour	White
Operating temperature (°C)	-40 to +60
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1
Compliant to	RoHS, Reach/SVHC