

# Thin wall 2/1 blue heat-shrink tubing without adhesive 25/12.5 mm 4FT

## Aucun visuel

### Caracteristics

Référence Nouvelle-Zélande : **BIZ218063**  
 Color : **Blue**  
 Wall Ø before shrinking (mm) : **25**  
 Wall Ø after shrinking (mm) : **12.5**

### GENERAL INFORMATION

#### Description

Thin wall 2/1 heat-shrink tubing without adhesive.

#### Technical details

Thin wall, 2/1 shrinkage in length 1.2 meter.  
 Heat-shrink tubing in flexible flame retardant polyolefin (except clear).  
 Working temperature: -45 °C to +125 °C (clear is -45 °C to +105 °C).  
 Shrink temperature: 120 °C (clear is 105 °C).  
 Dielectric strength (IEC 243): 15 kV/mm.  
 Tensile strength: 10.4 Mpa.  
 Rate voltage: 600 V.  
 Self-extinguishing in accordance with UL224 (except clear).

#### Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

### ADDITIONAL INFORMATION

Color and diameter next pages.

### LOGISTIC INFORMATION

#### Packaging



##### No packaging

Height (cm) : 1.25  
 Length (cm) : 120  
 Depth (cm) : 3.8  
 Net weight (kg) : 0.065  
 Gross weight (kg) : 0.068



#### Outer package 1



##### Bag

Height (cm) : 16  
 Length (cm) : 120  
 Depth (cm) : 3.8  
 Net weight (kg) : 0.65  
 Gross weight (kg) : 0.68



#### Outer package 2



##### Carton box

Height (cm) : 16  
 Length (cm) : 130  
 Depth (cm) : 20  
 Net weight (kg) : 14.5  
 Gross weight (kg) : 15.1



#### Outer package 3



##### Pallet

Height (cm) : 115  
 Length (cm) : 130  
 Depth (cm) : 80  
 Net weight (kg) : 406  
 Gross weight (kg) : 422.8

