

TECHNICAL DATA

SUPREME HEAVY DUTY

Automatic Hand Dryer 2kW





Height recommendations

Recommended height to bottom of dryer.

Men's washroom 1100mm Ladies' washroom 1050mm 13-17yrs 1000mm Children's washroom Children's washroom 10-13yrs 950mm 7-10yrs 900mm Children's washroom Children's washroom 4-7yrs 800mm Disabled Person's 950mm



MODEL BA101-E3

Motor 190W, 6670rpm, tropic proofed.

Sound levels 65DB (A) @1.5m

Fan Glass reinforced nylon flame retardant

Injection moulded, delivery 4.25 cubic meters

air per minute.

Element 2.0kW, heavy duty, protected by a resettable

cut-out at 95C and thermal fuse

Rating 9.8amps, @ 240VAC. IP22

Start-stop Electronic, infrared sensor

Cover ABS/ Polycarbonate blend—white

Dimensions 320mm wide x 325mm high x 190mm deep

Weight 3.8kg approx

Warranty Supreme 24 month limited warranty

Standards IEC 60335-2-23, AS/NZ 3350.2.23 1997

BS EN 60335-2-23 1997

CISPR 14-1 2000.

SAMPLE SPECIFICATION

Supreme BA101 automatic hand dryer

General

Scope:- Supply and install Supreme BA101 automatic hand dryer as shown on the plans

Materials

Primary Materials:-Supreme BA101 electrical automatic hand dryer complete with white ABS/ Polycarbonate cover

Workmanship

Remove Hand Dryer cover:- remove 2 x 6mm screws on the underside of the dryer. Lift lower part of the cover forward approximately 12mm then push cover upwards to unlatch top of cover from back plate. Position back plate on the wall with 320mm width to the top and height 325mm to the left side as you face the dryer.

Washrooms Mount at recommended height from floor varies, refer chart opposite

Fasten dryer to the wall using 4 only wood screws or 6mm toggle bolts for steel framed walls or 6mm masonry anchors for masonry walls.

Electrical connection to be made by hard wiring back to isolating switch mounted in a convenient position in accordance with Electrical Codes of Practice.

Plug sensor leads from cover to printed circuit board. Replace cover, latch top of cover onto back plate, ease bottom of cover into place and then replace the 2 only 6mm screws.

Completion

Leave work clean, remove all trade rubbish from the site and leave the hand dryer cleaned and in working order.

Pass over warranties/manuals (supplies 24 months material and workmanship guarantee) to the principal. Give maintenance instructions to principal.

We reserve the right to alter specifications and design without prior notice